◆ INPUT CHARACTERISTICS:

- VOLTAGE: 90VAC TO 264VAC
- FREQUENCY: 50 ~60 HZ
- INPUT CURRENT: 2A MAX
- INRUSH CURRENT: 40A 115VAC;60A 230VAC

◆ SPECIFICATION:

- EFFICIENCY: 85% MAXIMUM FOR NOM LOAD.
- OPERATING TEMPERATURE RANGE: 0℃ ~ 40℃.
- PROTECTION: DC OUTPUT OVP, DC OUTPUT OCP, DC OUTPUT SCP,.
- EMI REQUIREMENT: EN55022,CLASS B, GB9254-1998, FCC CLASSB
- SAFETY: UL60950, EN60950, GB4943-2001
- DIMENSION: 170 (D) x 64 (W) x 34.5 (H) mm.
- COOLING: VENTILATION COOLING.

◆ OUTPUT CHARACTERISTICS:

OUTPUT VOLTAGE	OUTPUT CURRENT		REGULATION	
	MIN [A]	MAX [A]	LOAD	LINE
+24V	0	3.95	±5%	±1%
+20V	0	4.5	±5%	±1%
+19V	0	4.75	±5%	±1%
+18V	0	5	±5%	±1%
+16V	0	5.3	±5%	±1%
+15V	0	5.5	±5%	±1%
+5VUSB	0	1	±5%	±1%

1. MAXIMUM CONTINUOUS TOTAL DC OUTPUT POWER SHALL NOT EXCEED 100W.